

# DisklessWorkstations.Com

360 East Maple Rd, Suite C  
Troy, Michigan 48083  
Phone: (888) DLW-LTSP  
Fax: (248) 577-0201

Web: [www.DisklessWorkstations.Com](http://www.DisklessWorkstations.Com)  
Email: [diskless@DisklessWorkstations.Com](mailto:diskless@DisklessWorkstations.Com)

## Thank you for purchasing a LTSP Term 1000 PXE Thin Client!

The LTSP Term 1000 features a 200 MHz Vortex processor, 128mb of RAM and a graphics resolution up to 1280x1024.

### Features:

- Supports 32 bit color at 1280 x 1024
- Supports attached local devices -- USB printers, barcode scanner, USB CD-ROM and more
- 10/100 Base-T Ethernet
- PXE Bootrom
- VESA Mountable
- Low Power +5V @3A
- Compact, Reliable and Silent.

### Specifications:

#### Operating Software:

- . PXE Network Booting
- . LTSP Ready

#### CPU:

- . Vortex86 SoC-200MHz (Fanless, x86 compatible)

#### Memory:

- . 128MB SDRAM on board
- . 128 MB max.

#### Display:

- . SIS Integrated Graphics Core
- . Shared System memory 8MB
- . 1024 x 768 / up to 85 Hz/ 32 Bit
- . 1280 x 1024 / up to 85 Hz/ 32 Bit

#### Audio:

- . AC97 CODEC, Fully Compliant with AC97 V2.1
- . Phone Jack for MIC-in and Line-Out

#### Networking:

- . 10/100 Base-T Realtek 8100B Fast Ethernet

#### I/O Connectors:

- . Analog VGA video output, DB-15 connector
- . Three USB 1.1 ports(two at front, one at rear)
- . One PS/2 port for mouse or keyboard
- . RTL 8100B 10/100 Mbit, one RJ-45 connector
- . Enhanced IDE interface, 44pin box header x 1
- . Type I/II Compact Flash Slot x 1

#### LED Indicators:

- . One Power indicator (On front bezel)
- . Two Network adapter indicators (On rear panel)

#### Warranty:

- . One year from date of invoice.

#### Power Supply:

- . External, auto sensing
- . Input: 100-240V @ 50~60Hz

#### Dimensions: (W X H X D)

- . 115 x 35 x 115 mm

#### Weight:

- . Unit 500 g
- . Shipping 750 g

#### Regulatory Compliance:

- . Emissions FCC UL,CE

#### Temperature:

- . Operating: 32F~140F (0C~60C)