

## Thank you for purchasing a LTSP Term 170 Thin Client!

The LTSP Term 170 features a 1 GHz Via Eden processor, 256mb of DDR SDRAM and a graphics resolution up to 1600x1200, making this one of the most powerful thin clients available.

**NOTE:** Because of the advanced graphics chipset, this unit **requires LTSP v4.1** or newer!

### Check for LTSP updates with `ltsadmin`.

**NOTE:** Add the following option to the `lts.conf` file for each LTSP Term 170 workstation to correct video RAM detection. If you adjust the video ram in the BIOS set this value accordingly.

```
[wsXXX]  
X_VIDEORAM = 16384
```

### Features:

- Supports up to 16-bit color at 1600 x 1200
- Supports attached local devices including printers, barcode scanners and more
- 10/100 Base-T Fast Ethernet
- USB 2.0
- Compact, Durable, Silent and low power consumption

### Specifications:

|                            |   |
|----------------------------|---|
| <b>Operating Software:</b> | Integrated PXE Module for Network booting<br>in an <b>LTSP 4.1</b> environment.   |
| <b>CPU:</b>                | 1 GHz Via Eden Processor (Fanless, x86 compatible)  |
| <b>Memory:</b>             | 256MB DDR SDRAM (512MB max)   |
| <b>Video chipset:</b>      | Embedded Via CLE266 VGA, 8x AGP up to 64MB shared memory<br>(Requires X.org X11R6.7, included in LTSP-4.1)<br>Maximum resolution 1600 X 1200, 85 Hz, 16-bit high color<br>800 x 600 / 32-bit up to 85 Hz<br>1024 x 768 / 32-bit up to 85 Hz<br>1280 x 1024 / 16-bit up to 85 Hz<br>1600 x 1200 / 16-bit up to 85 hz                         |
| <b>Networking:</b>         | 10/100 Base-T Fast Ethernet, Wake-On-Lan ready  |
| <b>I/O Connectors:</b>     | One DC Power Inlet<br>One RJ-45 for 10/100 Base-T Ethernet<br>Two Mini-DIN6F for keyboard & mouse<br>One serial port DP9M connector RS-232C, up to 115.2K baud<br>One parallel port DB25F connector bi-directional Centronics compatible<br>Audio Line-in, Headphone-out, Microphone in<br>One DB15F for video output<br>Four USB 2.0 ports |
| <b>LED Indicators:</b>     | One Power indicator (At front bezel)<br>One Network activity indicator on front bezel<br>Two Network adapter indicators (At rear panel)   |
| <b>Warranty:</b>           | 1 year from date of invoice   |
| <b>Power Supply:</b>       | Input: 90-264V @ 50-60Hz  |
| <b>Dimensions:</b>         | 2.0 x 9.1 x 8.3 inches (51 x 232 x 212 mm) (WxHxD)  |
| <b>Weight:</b>             | 4.5 lbs (2.2 kgs)   |
| <b>Safety/Regulations:</b> | FCC class B, CE, CUL, TUV, BSMI, C-TICK, CB   |
| <b>Temperature:</b>        | Operating: 41~104 degree F (5~40 C)<br>Storage: -40~140 F (-40~60 C)  |
| <b>Humidity:</b>           | Operating: 20% to 80% non-condensing<br>Storage 20% to 80% non-condensing   |